# Robo-Drain

## Model: RD750

6.00

#### **FEATURES & BENEFITS:**

- Isolated Trigger Assembly Reliable design; unaffected by contaminants
- Stainless Steel Reservoir Durable for high pressure capacity
- Non Clogging, Full Port Drain Valve Handles scale & rust without clogging
- Horizontal Low Profile Fits in tight spots; can be mounted under equipment
- Heavy Duty Industrial Drain Ideal for high pressure compressor installations
- Fully Automatic & Pneumatic Design Operates on demand without the need for electricity
- Large 24 oz. Capacity Discharge One unit works for multiple compressed air systems. Saves valuable air & money.

### **SPECIFICATIONS**

INLETS: (2) 3/4" NPT or BSP

OUTLET: 1/2" NPT or BSP

POWER: Clean, Dry Compressed Air • 80 to 130 PSI

PRESSURE: 0 to 750 PSI

OPERATING TEMP: 32° to 180° F

WEIGHT: 22 lbs.

10.50

DISCHARGE: 24 ounces per cycle



#### **MATERIALS HEADS:** Aluminum VESSEL: 304L Stainless Steel VALVE: Stainless Steel with Stainless Steel Ball & Stem FLOAT: Stainless Steel SEAT: Stainless Steel SEAL: Viton 9.06 14.50 (REF) 1.81 3.00 6.06 10.88 (REF) VENT LINE 1/8 NPT CHECK VALVE AIR FILTER TEST BUTTON 1.50 (0)Ø 3.85 (REF) 6.50 5.25 1.69 Ø

3.00 -INLET 3/4 NPT (OPTIONAL LOCATION) Air System Products

